

Lokset[®] Resin Capsule



Product Information Sheet

Capsule	Description	Capsule Colour	Label Colour	Approx Spin Time (secs)	Approx Hold Time (secs)	Gel time 25°C (secs)
SF	Super Fast	Yellow	White	8	> 4	10 - 11
XF	Extra Fast	Yellow	Orange	8	> 4	12 - 13
F	Fast	Yellow	Yellow	10	> 4	15 - 16
M	Medium	Red	Red	15	> 4	19 - 23
M	Medium - J Series	Red	Red	12	Tension > 5 mins	15 - 23
S	Slow	Blue	Blue	20	> 70	80 - 140
S	Slow - J Series	Blue	Blue	20	Tension > 10 mins	60 - 110
FRS	Flexibolt Resin Slow	L Green	Green	20	> 120	100 - 160
FRXS	Flexibolt Resin Extra Slow	L Purple	Purple	20	> 300	300 - 420
FRXXS	Flexibolt Resin Extra Extra Slow	L Pink	Pink	20	> 1200	1200 - 1500
XFM	Extra Fast/Medium 50:50 TOOSPEEDIE [®]	Yellow/Red	Orange/ Red Vertical	11	12 - 19	-
SFS	Super Fast/Slow TOOSPEEDIE [®]	Yellow/Blue	White/ Blue Vertical	11	10 - 60	-
FS	Fast/Slow 50:50 TOOSPEEDIE [®]	Yellow/Blue	Yellow/ Blue Vertical	14	12 - 60	-
MS	Medium/Slow 50:50 TOOSPEEDIE [®]	Red/Blue	Red/Blue Vertical	16	19 - 60	-
XFS	Extra Fast/Slow 40:60	Yellow/Blue	Orange/ Blue Diagonal	12	12 - 60	-
FS	Fast/Slow 40:60	Yellow/Blue	Yellow/ Blue Diagonal	14	12 - 60	-
MS	Medium/Slow 40:60	Red/Blue	Red/Blue Diagonal	16	19 - 60	-
XFS	XFast Slow 50:50 TOOSPEEDIE [®]	Yellow/Blue	Orange/ Blue Vertical	12	12 - 60	-

Minova Australia Pty Ltd
A.B.N. 78 084 965 962
 102 Albatross Road, Nowra
 PO Box 554, Nowra NSW 2541
 Tel: +61 (0)2 4421 4377
 Fax: +61 (0)2 4422 1637
 Solutions@MinovaInt.com
 www.minovainternational.com



A member of the Orica Group

■ Flexibolt resins, FRS, FRXS and FRXXS capsules are made from a specially formulated resin mastic to aid insertion and push through where long tendon support systems are used e.g. Flexibolts.

■ Minova J Series resins are used as an anchoring support in strata where large annular gaps between bolt and hole diameters are encountered. The tensioning time may be dependent on the degree of tension required in tonnes.

■ See product data sheets for more information, which are available on our website.

All information contained in this document is provided in accordance with Minova Australia's "Standard Conditions of Sale", available at www.minova.com.au.

While Minova Australia makes every effort to ensure the details contained in this data sheet are as current and accurate as possible, the conditions under which its products are used are not within Minova Australia's control. The information on this data sheet is subject to change without notice. Each user is responsible for being aware of the details in the data sheet and the product applications in the specific context of the intended use. The results may depend on the conditions under which the products are stored, transported and used.

Buyers and users assume all risk, responsibility and liability arising from the use of this product and the information in this data sheet. Minova Australia is not responsible for damages of any nature resulting from the use of its products or reliance upon the information. Minova Australia makes no express or implied warranties.

MIN AUS/MS2219/08/O
© Registered Trademark of Minova International Limited
Copyright 2003, 2004 Minova Australia Pty Ltd